


# H 4300 Woltmann meter

The hot water flow sensor for installation in any orientation



Approval								
<table border="1"><tr><td>22.56</td></tr><tr><td>01.01</td></tr></table>	22.56	01.01	<table border="1"><tr><td>22.16</td></tr><tr><td>87.01</td></tr></table>	22.16	87.01	<table border="1"><tr><td>22.56</td></tr><tr><td>03.02</td></tr></table>	22.56	03.02
22.56								
01.01								
22.16								
87.01								
22.56								
03.02								
WP DN 50/65	WP DN 80 ... DN 125	WP DN 150/200						

- Woltmann meter flow sensor WP for hot water
- Nominal size DN 50 up to 200
- High temperature load up to 120 °C
- Highly durable tungsten carbide/  
sapphire jewel rotor bearings
- Serial pulse output



<b>Woltmann meter WP</b>		<b>H 4300</b>							
Nominal size / Connection flange		DN	50	65	80	100	125	150	200
Meter size / Nominal flow rate		Q <sub>n</sub> (Q <sub>p</sub> )	15	25	40	60	100	150	250
<b>Ordering number</b>	Initial certification class A*								
Litres/pulse			100	100	100	100	100	1000	1000
PN10	4-hole (old standard)		—	—	<b>0002009</b>	—	—	—	<b>0002014</b>
PN16			<b>0002007</b>	<b>0002008</b>	<b>0002010</b>	<b>0002011</b>	<b>0002012</b>	<b>0002013</b>	<b>0002015</b>
L Length	mm		200	200	225	250	250	300	350
B Width	mm		155	155	200	220	250	285	340
H <sub>1</sub> Centerline height	mm		75	83	92	110	125	135	163
H <sub>2</sub> Overall height	mm		200	206	292	310	325	379	407
Weight	kg		11	11.5	18	20	22.4	39	47
<b>Performance characteristics</b>									
Maximum flow rate	Q <sub>max</sub> (Q <sub>s</sub> )	m <sup>3</sup> /h	30	30	90	200	200	300	500
Minimum flow rate	Q <sub>min</sub> (Q <sub>i</sub> )	m <sup>3</sup> /h	0.55	0.55	2	2.4	3.5	4.5	8
Starting flow		m <sup>3</sup> /h	0.13	0.13	0.27	0.5	0.8	1.7	2.0
Continuous loading		m <sup>3</sup> /h	50	70	40	60	100	450	800
Temperature**	T <sub>max</sub>	°C	120	120	120	120	120	120	120
Pressure rating	PN	bar	16	16	10/16	16	16	16	10/16
Flow capacity	at 0.1 bar pressure loss	m <sup>3</sup> /h	35	63	85	95	200	310	560

\* other types on request

\*\* Register heightening for T<sub>max</sub> 130 °C on request

#### Contact output

Version Reed switch potted,  
Protection class IP 68

Contact load max. 24 V DC, 200 mA

Resistance 100 Ohm/0.25 W


Cable length 3 m

#### Pulse value

Available pulse sequences: 25 - 100 - 250 - 1000 litres/pulse

Standard version DN 50-125: 100 litres/pulse

Standard version DN 150-200: 1000 litres/pulse



Elster Metering Limited  
130 Camford Way, Sundon Park  
Luton, Bedfordshire LU3 3AN  
United Kingdom

T +44 (0) 1582 846 400  
F +44 (0) 1582 564 728  
E water.metering@gb.elster.com

www.elstermetering.com  
Copyright © 2010 Elster Group  
8511C6346

All rights reserved.  
No part of the publication may be reproduced in any material form without the written permission of the Elster Group except in accordance with the provisions of the Copyright, Designs and Patents Act 1988.  
The Company's policy is one of continuous improvement and the right is reserved to modify the specifications without notice.

